



**BAV70S**

Preliminary

**DIODE**

**DUAL SURFACE MOUNT SWITCHING DIODE**

■ DESCRIPTION



The UTC **BAV70S** is a dual surface mount switching diode providing the designers high switching speed, high conductance and high reliability.

The UTC **BAV70S** is suitable for common switching applications.

■ FEATURES

- \* High Switching Speed
- \* High Conductance
- \* High Reliability
- \* Low capacitance
- \* Reverse voltage
- \* Low leakage current

■ SYMBOL




■ ORDERING INFORMATION

Ordering Number		Package	Pin Assignment						Packing
Lead Free	Halogen Free		1	2	3	4	5	6	
BAV70SL-AL6-R	BAV70SG-AL6-R	SOT-363	A1	A1	K2	A2	A2	K1	Tape Reel

Note: Pin Assignment: A: Anode K: Cathode

<p>BAV70SG-AL6-R</p> <ul style="list-style-type: none"> <li>(1) Packing Type</li> <li>(2) Package Type</li> <li>(3) Green Package</li> </ul>	<ul style="list-style-type: none"> <li>(1) R: Tape Reel</li> <li>(2) AL6: SOT-363</li> <li>(3) G: Halogen Free and Lead Free, L: Lead Free</li> </ul>
--	---

■ MARKING



■ ABSOLUTE MAXIMUM RATINGS ( $T_A = 25^\circ\text{C}$  unless otherwise specified)

PARAMETER	SYMBOL	RATINGS	UNIT
Non-Repetitive Reverse Voltage	$V_{RM}$	100	V
Peak Repetitive Reverse Voltage	$V_{RRM}$	75	V
Working Peak Reverse Voltage	$V_{RWM}$	75	V
DC Blocking Voltage	$V_R$	75	V
Forward Continuous Current (Note 2)	$I_F$	150	mA
Average Rectified Output Current (Note 2)	$I_O$	75	mA
Repetitive Peak Forward Current (Note 2)	$I_{FRM}$	500	mA
Non-Repetitive Peak Forward Surge Current (Note 2)	$t = 1.0\mu\text{s}$	4	A
	$t = 1.0\text{ms}$	1	A
	$t = 1.0\text{s}$	0.5	A
Power Dissipation	$P_D$	350	mW
Operating Temperature	$T_J$	-65 ~ +150	$^\circ\text{C}$
Storage Temperature	$T_{STG}$	-65 ~ +150	$^\circ\text{C}$

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Device mounted on FR-4 substrate PC board, 2oz copper, with 1inch square copper plate.

■ THERMAL DATA

PARAMETER	SYMBOL	RATINGS	UNIT
Typical Thermal Resistance	$\theta_{JA}$	500	$^\circ\text{C/W}$

■ ELECTRICAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$  unless otherwise specified.)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Reverse Breakdown Voltage (Note 1)	$V_{(BR)R}$	$I_R = 0.5\mu\text{A}$	85			V
Forward Voltage (Note 2)	$V_F$	$I_F = 1.0\text{mA}$			0.715	V
		$I_F = 10\text{mA}$			0.855	V
		$I_F = 50\text{mA}$			1	V
		$I_F = 150\text{mA}$			1.25	V
Reverse Current	$I_R$	$V_R = 25\text{V}$			30	nA
		$V_R = 80\text{V}$			0.5	$\mu\text{A}$
		$V_R = 25\text{V}, T_J = 150^\circ\text{C}$			30	$\mu\text{A}$
		$V_R = 80\text{V}, T_J = 150^\circ\text{C}$			100	$\mu\text{A}$
Reverse Recovery Time	$t_{rr}$	$I_F = I_R = 10\text{mA}, I_{rr} = 0.1I_R, R_L = 100\Omega$			4	ns

Notes: 1. Short duration test pulse used to minimize self-heating effect.

2. Pulse Test: Pulse width  $\leq 300\mu\text{s}$ , Duty cycle  $\leq 1\%$ .

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.