



UMUR2040C

DIODE

SWITCHMODE POWER RECTIFIERS

DESCRIPTION


The UTC **UMUR2040C** is a switchmode power rectifier, it uses UTC's advanced technology to provide customers with high voltage capability, low forward drop and low leakage current, etc.

The UTC **UMUR2040C** is suitable for use in switching power supplies, inverters and as free wheeling diodes.

FEATURES

- * Ultrafast and nanosecond recovery time
- * High voltage capability
- * Low forward drop
- * Low leakage current

SYMBOL




ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
UMUR2040CL-TA3-T	UMUR2040CG-TA3-T	TO-220	A	K	A	Tube
UMUR2040CL-T3F-T	UMUR2040CG-T3F-T	TO-3PF	A	K	A	Tube

Note: Pin Assignment: A: Anode K: Cathode

 UMUR2040CG-TA3-T (1) Packing Type (2) Package Type (3) Green Package		(1) T: Tube (2) TA3: TO-220, T3F: TO-3PF (3) G: Halogen Free and Lead Free, L: Lead Free
---	--	--

MARKING



■ ABSOLUTE MAXIMUM RATINGS

PARAMETER		SYMBOL	RATINGS	UNIT
Repetitive Peak Reverse Voltage		V_{RRM}	400	V
Working Peak Reverse Voltage		V_{RWM}	400	V
DC Blocking Voltage		V_R	400	V
Average Forward Current	$T_C=100^{\circ}\text{C}$	I_O	10	A
	Total Device		20	A
Nonrepetitive Peak Surge Current (Surge applied at rated load conditions, halfwave, single phase, 60 Hz)		I_{FSM}	105	A
Operating Junction Temperature		T_J	-65 ~ +150	$^{\circ}\text{C}$
Storage Temperature		T_{STG}	-65 ~ +150	$^{\circ}\text{C}$

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ THERMAL DATA

PARAMETER		SYMBOL	RATINGS	UNIT
Junction to Case	TO-220	θ_{JC}	2	$^{\circ}\text{C}/\text{W}$
	TO-3PF		1.5	$^{\circ}\text{C}/\text{W}$

■ ELECTRICAL CHARACTERISTICS

Single phase, half wave, 60Hz, resistive or inductive load.



For capacitance load, derate current by 20%.

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Reverse Breakdown Voltage (Note 1)	$V_{(BR)R}$	$I_R=1\text{mA}$	400			V
Forward Voltage Drop	V_{FM}	$I_F=10\text{A}, T_C=25^{\circ}\text{C}$			1.5	V
		$I_F=10\text{A}, T_C=150^{\circ}\text{C}$			1.4	V
Leakage Current (Note 1)	I_{RM}	Rated DC voltage, $T_J=150^{\circ}\text{C}$			10	μA
		Rated DC voltage, $T_J=25^{\circ}\text{C}$			250	μA
Maximum Reverse Recovery Time	t_{rr}	$I_F=1.0\text{A}, di/dt=50\text{A}/\mu\text{s}$		46	60	ns

Notes: 1. Short duration pulse test used to minimize self-heating effect.

2. Thermal resistance junction to case mounted on heatsink.

■ TYPICAL CHARACTERISTICS



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.