

USC065R260B

Power MOSFET

15.5A, 650V N-CHANNEL SILICON CARBIDE PLANAR ENHANCEMENT POWER MOSFET



TO-252



PDFN5×6

■ DESCRIPTION


SiC The material can achieve high voltage with most carrier devices (MOSFET) with fast device structure characteristics, so it can realize the three characteristics of "high voltage", "low on resistance" and "high frequency" at the same time.

It is widely used in electric vehicle charger, industrial equipment power supply, efficient power regulator inverter and rectification part and other uses.


■ FEATURES

* $R_{DS(ON)} \leq 300\ m\Omega$ @ V_{GS}=15V, I_D=5.0A
* Wide bandgap SiC MOSFET technology
* High Blocking Voltage with Low On-Resistance
* High Speed Switching with Low Capacitances
* High-Speed And High Robust Intrinsic Body Diode

■ SYMBOL



TO-252



PDFN5×6

Copyright © 2026 Unisonic Technologies Co., Ltd



■ ORDERING INFORMATION

Ordering Number		Package	Pin Assignment								Packing
Lead Free	Halogen Free		1	2	3	4	5	6	7	8	
USC065R260BL-TN3-R	USC065R260BG-TN3-R	TO-252	G	D	S	-	-	-	-	-	Tape Reel
USC065R260BL-P5060-R	USC065R260BG-P5060-R	PDFN5×6	S	S	S	G	D	D	D	D	Tape Reel

Note: Pin Assignment: G: Gate D: Drain S: Source

USC065R260BG-TN3-R (1)Packing Type (2)Package Type (3)Green Package	(1) R: Tape Reel (2) TN3: TO-252, P5060: PDFN5×6 (3) G: Halogen Free and Lead Free, L: Lead Free

■ MARKING

TO-252	PDFN5×6
	

■ ABSOLUTE MAXIMUM RATINGS (T_C=25°C, unless otherwise specified)

PARAMETER			SYMBOL	RATINGS	UNIT
Drain-Source Voltage			V_{DSS}	650	V
Gate-Source Voltage	Dynamic		V_{GSS}	-10 / +22	V
	Static			0 / +15	V
Drain Current	Continuous	T_C=25°C	I_D	15.5	A
		T_C=100°C		11	A
	Pulsed (Note 2)		I_{DM}	25	A
Power Dissipation		TO-252	P_D	67	W
		PDFN5×6		90	W
Junction Temperature			T_J	-55 ~ +175	°C
Storage Temperature			T_{STG}	-55 ~ +175	°C

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.
2. Repetitive Rating: Pulse width limited by maximum junction temperature.

■ THERMAL DATA

PARAMETER		SYMBOL	RATINGS	UNIT
Junction to Case	TO-252	θ_{JC}	2.23	°C/W
	PDFN5×6		1.67	°C/W


Notes: 1. The maximum current rating is package limited.
2. Pulse Test Pulse Width ≤ 10ms, Duty Cycle ≤ 1%.

■ ELECTRICAL CHARACTERISTICS (T_J=25°C, unless otherwise specified)


PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS						
Drain-Source Breakdown Voltage	BV_{DSS}	I_D=100μA, V_{GS}=0V	650			V
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=650V, V_{GS}=0V		0.1	20	μA
Gate- Source Leakage Current	I_{GSS}	V_{GS}=-10/+22V, V_{DS}=0V			±250	nA
ON CHARACTERISTICS						
Gate Threshold Voltage	$V_{GS(TH)}$	V_{DS}=V_{GS}, I_D=10mA	3.2	4.1	5.0	V
		V_{DS}=V_{GS}, I_D=10mA, T_J=175°C		2.9		V
Static Drain-Source On-State Resistance	$R_{DS(ON)}$	V_{GS}=15V, I_D=5.0A		260	300	mΩ
		V_{GS}=15V, I_D=5.0A, T_J=175°C		231		mΩ
Transconductance	g_{FS}	V_{DS}=20V, I_D=5.0A		3.6		S
DYNAMIC PARAMETERS						
Input Capacitance	C_{ISS}	V_{DS}=650V, V_{GS}=0V, f=1MHz		294		pF
Output Capacitance	C_{OSS}			25		pF
Reverse Transfer Capacitance	C_{RSS}			4		pF
SWITCHING PARAMETERS						
Total Gate Charge	Q_G	V_{DS}=400V, V_{GS}=0V / +15V, I_D=5.0A		12.5		nC
Gate to Source Charge	Q_{GS}			4.3		nC
Gate to Drain Charge	Q_{GD}			1.6		nC
Internal Gate Input Resistance	R_G	V_{AC}=25mV, f=1MHz		25.5		Ω
Turn-on switching energy	E_{ON}	V_{DS}=400V, V_{GS}=0V / +15V, I_D=5.0A, R_G=2.2Ω, L=600μH		43.2		μJ
Turn-off switching energy	E_{OFF}			5.5		μJ
Turn-ON Delay Time	$t_{D(ON)}$			6.6		ns
Rise Time	t_R			18.3		ns
Turn-OFF Delay Time	$t_{D(OFF)}$			17.7		ns
Fall-Time	t_F			32.1		ns
SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS						
Drain-Source Diode Forward Voltage	V_{SD}	V_{GS}=0V, I_{SD}=2.5A, T_J=25°C		3.3		V
		V_{GS}=0V, I_{SD}=2.5A, T_J=175°C		2.8		V
Continuous Diode Forward Current	I_S				12	A
Body Diode Reverse Recovery Time	t_{rr}	V_{GS}=0V, I_F=5.0V, V_R=400V, d_{IF}/dt=1600A/μs		9.9		ns
Body Diode Reverse Recovery Charge	Q_{rr}			32.6		nC
Peak Reverse Recovery Current	I_{rrm}			5.8		A

■ TYPICAL CHARACTERISTICS


Output Characteristics




Output Characteristics




Output Characteristics




Drain-Source On-Resistance vs. Junction Temperature



Transfer Characteristic For Various Junction Temperatures




Gate Threshold Voltage vs. Internal Equivalent Temperature




■ TYPICAL CHARACTERISTICS (Cont.)


Body Diode Characteristics




Body Diode Characteristics




Body Diode Characteristics




Capacitances Characteristics




Gate Charge Characteristics



Power Dissipation



■ TYPICAL CHARACTERISTICS (Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.